


SPECIFICATIONS


Current Rating: 0.75 AMP
 Contact Resistance: 20mΩ Max.
 Withstand Voltage: AC/DC 500V
 Insulator Resistance: 1000 MΩ Min
 Operating Temp.: -40°C ~ +105°C
 Contact Material: Brass
 Contact Plating: Au or Sn over Ni
 Insulator Material: PA6T Black+30%GF UL94V-0 BK



| PIN Number | Dimension (mm) | | PIN Number | Dimension (mm) | |
|------------|----------------|-------|------------|----------------|-------|
| | A | B | | A | B |
| 2*2P | 1.00 | 2.00 | 2*27P | 26.00 | 27.00 |
| 2*3P | 2.00 | 3.00 | 2*28P | 27.00 | 28.00 |
| 2*4P | 3.00 | 4.00 | 2*29P | 28.00 | 29.00 |
| 2*5P | 4.00 | 5.00 | 2*30P | 29.00 | 30.00 |
| 2*6P | 5.00 | 6.00 | 2*31P | 30.00 | 31.00 |
| 2*7P | 6.00 | 7.00 | 2*32P | 31.00 | 32.00 |
| 2*8P | 7.00 | 8.00 | 2*33P | 32.00 | 33.00 |
| 2*9P | 8.00 | 9.00 | 2*34P | 33.00 | 34.00 |
| 2*10P | 9.00 | 10.00 | 2*35P | 34.00 | 35.00 |
| 2*11P | 10.00 | 11.00 | 2*36P | 35.00 | 36.00 |
| 2*12P | 11.00 | 12.00 | 2*37P | 36.00 | 37.00 |
| 2*13P | 12.00 | 13.00 | 2*38P | 37.00 | 38.00 |
| 2*14P | 13.00 | 14.00 | 2*39P | 38.00 | 39.00 |
| 2*15P | 14.00 | 15.00 | 2*40P | 39.00 | 40.00 |
| 2*16P | 15.00 | 16.00 | 2*41P | 40.00 | 41.00 |
| 2*17P | 16.00 | 17.00 | 2*42P | 41.00 | 42.00 |
| 2*18P | 17.00 | 18.00 | 2*43P | 42.00 | 43.00 |
| 2*19P | 18.00 | 19.00 | 2*44P | 43.00 | 44.00 |
| 2*20P | 19.00 | 20.00 | 2*45P | 44.00 | 45.00 |
| 2*21P | 20.00 | 21.00 | 2*46P | 45.00 | 46.00 |
| 2*22P | 21.00 | 22.00 | 2*47P | 46.00 | 47.00 |
| 2*23P | 22.00 | 23.00 | 2*48P | 47.00 | 48.00 |
| 2*24P | 23.00 | 24.00 | 2*49P | 48.00 | 49.00 |
| 2*25P | 24.00 | 25.00 | 2*50P | 49.00 | 50.00 |
| 2*26P | 25.00 | 26.00 | | | |

Any size and shape can be customized.
 Contact sales team for more information.



| | | | | | | | |
|--|-------|-------|------------------|---|-------|----------|------------|
| PRODUCT NAME | DIM | TOL | DWG NO. | DRAW | Wu | PART NO | CUST |
| 1.0 MM SINGLE ROW PIN HEADER SERIES | X.X | ±0.4 | P.W | CHECK | Tomy | UNIT | DATE |
| | X.XX | ±0.25 | MATER PA6T、BRASS | APPR | Allan | MM[INCH] | XXXX.XX.XX |
| | ANGLE | ±3° | REV. AO |  东莞市同盈电子有限公司 DONGGUAN WIN-WIN ELECTRONIC Co.,Ltd. | | | |